

LUX



LUX KONO Smart Thermostat

The attractive, full-featured thermostat

The stylish LUX KONO is more than just a pretty face. It combines elegant visual design with efficiency, comfort and convenience. It blends in or stands out with its interchangeable Décor-Snap Covers, which are available in eight colors. In addition, it seamlessly connects to many smart hubs, and is jam-packed with smart features like Home & Away Aware™. What's more, the KONO is one of the few thermostats that can pair with all three major voice assistants: Amazon Alexa, Google Assistant and Apple HomeKit.

Our goal at LUX is to design products around our customers, to make their lives easier and more comfortable. The attractive, full-featured LUX KONO thermostat does that with style.

Smart Features

- Home & Away Aware™: Geofencing for Automatic Savings
- 7-Day Programmable
- Alerts: Room Temperature, Filter Replacement
- Smart Tips: For Savings and Seasonality
- IAQ Fan: To Circulate Indoor Air
- Utility: Demand/Response Capable
- Reporting: Energy and Run Time Usage
- Utility Rebates Available: See luxproducts.com

User-Friendlier Comfort

Pair the KONO with the all-new LUX mobile app to make it user-friendlier. The LUX app was designed to create an easier, more intuitive control experience. It boasts an informative home screen, a feature-rich scheduling interface, and a host of other easy-to-navigate components for controlling the KONO. The LUX app is available for iOS and Android.



The power behind **your mission**



Specifications	Model KN-S-MG1-B04
Dimensions	Height: 4.5" (114.3 mm), Width: 4.5" (114.3 mm), Depth: 1.0" (25.4 mm)
Heat/Cool Terminals	Heat: 2 stages Cool: 1 stage
Electrical Ratings	Voltage Range: 20-30V AC Max Avg. Current Draw: 120mA at 24V AC Output Rating: 1.5A resistive load per terminal, 4.2A resistive load combined load
Temperature Control Range	Control Range: 50°F to 90°F (10°C to 32°C) Display Range: 32°F to 99°F (0°C to 37°C)
Environmental Limits	Operating Limits: 14°F to 122°F (-10°C to 50°C) Storage Limits: -4°F to 140°F (-20°C to 60°C) Operating Humidity: 20% to 80% non-condensing Moisture and Dust: Up to IP20
WiFi Specifications	2.4GHz: 802.11 b/g/n, SHA256RSA data encryption, network commissioning through iOS/Android app, program and system settings stored on the device for setup and function
Compatible With	Universal compatibility with forced air, gas, oil and electric furnaces up to 2H/1C and heat pump systems with or without aux/emergency heat. Power with C-wire or LUX Power Bridge (included).
Not Compatible With	120V/240V line voltage systems, 2-wire heat
Packaging	Master Carton: 4 units UPC: 021079170098

System

- Conventional: Forced air, gas, oil and electric furnaces (up to 2H/1C)
- Heat Pumps: With or without aux/emergency heat
- Power: C-wire or LUX Power Bridge (included)

Connectivity

- Radio: WiFi certified 802.11 b/g/n
- Frequency: 2.4 GHz
- Encryption: TLS1.2
- Platforms: Amazon Alexa, Google Assistant, Apple HomeKit, IFTTT



Accessories

- Wall Plate: Included
- Power Bridge: Included
- Décor-Snap Covers™: One included, additional colors sold separately



Best at-a-distance display for easy reading

Comfortable wheel interface – access menus, setup and comfort control



Apple HomeKit™

Use of the Works with Apple HomeKit logo means that an electronic accessory has been designed to connect specifically to iPod touch, iPhone, or iPad, respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. Apple is a trademark of Apple Inc., registered in the U.S. and other countries. HomeKit is a trademark of Apple Inc.



Questions?

Contact LUX customer service at luxproducts.com/contact or call 856-234-8803.

The power behind your mission

PUBL-7995 (0322)

